



CGD-LD204(Round)



CGD-LD204(Square)



Specifications

| | | | |
|--------------------------|--|--|--------------|
| Input Voltage | Non-Dimmable | AC100-240V 50/60HZ; AC200-240V 50/60HZ | |
| | Dimmable | AC100-120V 50/60HZ; AC200-240V 50/60HZ | |
| LED Current | Constant Current 350mA | | |
| Light Source | 4014 SMD LED | | |
| Power | 8W ± 10% / 11W ± 10% (LD204 Round) 11W ± 10% / 15W ± 10% (LD204 Square) | | |
| CCT | 3000K/4000K/6000K | | |
| Beam Angle | 90° | | |
| Operation Temperature | -20°C-+50°C | | |
| Lamp working temperature | ≤ 60°C | | |
| Life Span | 50000Hours | | |
| CRI | >80 | | |
| Luminous Flux | 8W ± 10% (LD204 Round) | 3000K | 600 lm ± 5% |
| | | 4000K | 710 lm ± 5% |
| | | 6000K | 720 lm ± 5% |
| | 11W ± 10% (LD204 Round) | 3000K | 785 lm ± 5% |
| | | 4000K | 845 lm ± 5% |
| | | 6000K | 870 lm ± 5% |
| | 11W ± 10% (LD204 Square) | 3000K | 755 lm ± 5% |
| | | 4000K | 895 lm ± 5% |
| | | 6000K | 905 lm ± 5% |
| | 15W ± 10% (LD204 Square) | 3000K | 1115 lm ± 5% |
| | | 4000K | 1265 lm ± 5% |
| | | 6000K | 1335 lm ± 5% |
| Surface color | White | | |